



त्रिमूर्ति®

सुंदरता की पहचान

SUPERIOR QUICK BOND

SPECIFICATIONS



About Trimurti Superior Quick Bond

Trimurti Quick Bond is a unique mixture of polymer, selected sand fillers, and additives that make it coarse and improve its bonding properties.

It is a replacement for the conventional hacking process. A bonding agent is specially formulated as a plaster bonding agent for pre-treatment of smooth backgrounds such as RCC Column beams, slabs, and precast / shear walls.

It also has dual bonding features that provide mechanical as well as chemical grip and eliminates the risk of deboning gypsum, or sand cement plaster.

Technical Specifications

Bonding Strength	18x than Conventional Hacking => 1Mpa
Appearance	Green
Type	Colloidal Solution with Suspended Solids
Setting Time	24 hrs.
PH	Near 7
Pull Out Strength	4KN for Gypsum
Ambient Temp.	9-45° C
Shelf Life	12 Months From the Date of Manufacturing

Features & Benefits



Suitable For RCC Concrete Surfaces



Easy Single Coat Application



Easy To Applied By The Roller



Strong Durable Bonding



Fire Resistance & Energy Saver



The Formulation Is Designed For Ready To Use



Provides High Adhesive Strength Due To The Interlocking Of The Gypsum Plaster.



20 Times Faster Application Than Hacking



Labour Safety As Compared With The Hacking Process

Chemical Composition

Polymer Based Liquid (Colloidal solution with suspended solids)

Standard Compliance

As per ASTM – D7234

Packaging

1kg, 5kg, 10kg, 20kg

Coverage

30–32 Sq. Ft. /Kg



Surface Preparation

- » The surface should be clean, dry & free from mould oil/ Grease & any other agents.
- » Just before the Application of Quick Bond, Pre-Wetting must be done with the help of a Roller.



Mixing

- » Take a same/above size bucket you will apply all solution poured into a blank bucket and repeat the same process until particles move in the solution.
- » Mix Material properly with a clean rod to properly disturbed solids particles in the solution at the Application time.





Application

- 01 Use a good Quality Roller.
- 02 The Roller should be cleaned with water immediately after use.
- 03 Allow it to dry for around 24 hrs. Or, depending on the environmental condition.
- 04 After 24hrs. The surface is ready for plastering Gypsum plaster.

Health & Safety Precautions

- » At the time of Quick Bond Application wear the P.P.E (Personal Protective Equipment) Such as Mask, gloves & goggles.
- » Don't use the hand for the mixing of particles in place of a Clean Rod.
- » Avoid contact with eyes & Skin in case of Contact. Kindly flush thoroughly with clean water immediately. If the problem persists, then consult a physician on priority.

Trimurti Wall Care Products Pvt. Ltd.

F-639, MIA Extension, Alwar, Rajasthan-301030

☎ 011-45556144

✉ info@trimurtiproducts.com

www.trimurtiproducts.com



Scan for Catalogue



दैनिक जागरण
VOCAL
FOR
LOCAL N

gea
2022
By Anupam Kher

gea
2023
By Madhuri Dixit



Toll Free: 1800-1200-620